

View Online at <https://aerobasegroup.com/nsn/5930-00-356-3962>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.040 inches

**Overall Height:**

1.906 inches

**Overall Width:**

1.000 inches

**Case Material:**

Metal

**Actuator Length:**

1.570 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.906 inches

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.312 inches

**Actuator Adapter Style:**

Roller plunger

**Center To Center Distance Between Adapter Mounting Facilities Parallel To Length:**

2.350 inches

**Housing Height:**

1.000 inches

**Housing Length:**

3.040 inches

**Housing Width:**

1.000 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

0.190 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.350 inches

**Maximum Voltage Rating In Volts:**

450.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

6.0 ounces

**Switch Actuating Force:**

Between 10.0 ounces and 15.0 ounces

**Actuator Movement:**

Between 0.188 pretravel inches and 0.190 overtravel inches and 0.006 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 12.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0