## NSN 5930-00-356-4624



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-356-4624 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.000 inches **Body Length:** 1.940 inches **Body Width:** 0.687 inches **Body Height:** 0.950 inches **Unthreaded Mounting Hole Diameter:** 0.140 inches **Actuator Style:** Round **Actuator Diameter:** 0.280 inches **Actuator Height:** 0.410 inches **Actuator Free Position Height:** 1.100 inches **Maximum Voltage Rating In Volts:** 480.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 10.0 ounces **Switch Actuating Force:** 22.0 ounces **Actuator Movement:** Between 0.050 pretravel inches and 0.094 overtravel inches and 0.007 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 250.000 milliamperes resistive dc and 20.000 amperes resistive ac **Terminal Type And Quantity:** 3 screw Shelf Life: N/a **Unit Of Measure:** 

\_

Demilitarization:

No

## **NSN 5930-00-356-4624** Sensitive Switch - Page 2 of 2



Fiig:

A053a0