## NSN 5930-00-356-7669

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-356-7669

**Thread Class:** 

2a single mounting facility

Thread Length:

0.438 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Explosion proof

**Overall Length:** 

**3.722** inches

**Shaft Diameter:** 

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:** 

1.000 inches single actuator

**Overall Diameter:** 

1.718 inches

**Individual Section Quantity:** 

7

**Nonturn Device Type:** 

Flatted bushing at 3: 00 o'clock

**Operating Tempurature Range:** 

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 each section front

**Throw Quantity:** 

15 each section rear

**Mounting Method:** 

Threaded bushing w/panel seal single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 each section

**Switch Actuator Indexing Position Quantity:** 

15 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section rear

## NSN 5930-00-356-7669

Rotary Switch - Page 2 of 2



15.0 degrees single actuator

**Detent Rotational Torque Range:** 

+20.000/+80.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

500.0 milliamperes resistive load dc at altitude

**Style Designator:** 

Tap, circular, bushing mount

## **Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

Deminianzanc

No

Fiig:

A052b0