

View Online at <https://aerobasegroup.com/nsn/5930-00-357-0485>

Thread Length:

0.375 inches single mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

2.000 inches

First Flat Length:

0.344 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.500 inches single actuator

Overall Diameter:

2.125 inches

Nonturn Device Radius:

0.500 inches at 6: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 highest dc voltage rating at sea level

Shaft Flat/slot Angular Location:

30.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load lowest dc voltage rating at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0