NSN 5930-00-361-2597

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-361-2597

Body Style:
Bushing mounted
Overall Length:
1.466 inches
Overall Height:
0.500 inches
Overall Width:
0.500 inches
Body Diameter:
0.500 inches
Bushing Length:
0.545 inches
Body Length:
0.840 inches
Actuator Style:
Round
Actuator Diameter:
0.153 inches
Actuator Height:
0.057 inches
Actuator Free Position Height:
Between 0.612 inches and 0.626 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.438 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
20.0 ounces
Actuator Movement:
0.010 pretravel inches and 0.050 overtravel inches and 0.005 differential inches
Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes inductive dc

NSN 5930-00-361-2597 Sensitive Switch - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Thread Series Designator:
Un
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0