

View Online at <https://aerobasegroup.com/nsn/5930-00-364-3654>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.900 inches

Overall Width:

3.000 inches

Body Height:

4.750 inches

Unthreaded Mounting Hole Diameter:

Between 0.219 inches and 0.233 inches

Longest Horizontal Distance Between Mounting Centers:

2.120 inches

Longest Vertical Distance Between Mounting Centers:

2.120 inches

Fragility Factor:

Moderately rugged

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Base and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

350.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

3.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

45.00 actuation point pounds per square inch and 35.00 deactuation point pounds per square inch and 10.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0