NSN 5930-00-365-6333

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-365-6333

Thread Class:
2a single mounting facility
Thread Length:
0.375 inches single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.500 inches
Overall Height:
1.062 inches
Overall Width:
1.062 inches
First Flat Length:
0.375 inches single actuator
Shaft Length:
0.500 inches single actuator
Individual Section Quantity:
1
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
6 single section front
Throw Quantity:
2 single section rear
Mounting Method:
Threaded bushing single mounting facility
Features Provided:
Metallic inclosure
Thread Size:
0.375 inches single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Rotor Through Connection Quantity:
6 single section
Switch Actuator Indexing Position Quantity:
12 single actuator
Shaft Type:
Round, v flatted single actuator
Terminal Type:
Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

NSN 5930-00-365-6333

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 30.0 degrees single actuator Contact Load Current Rating: 750.0 milliamperes resistive load ac at sea level Precious Material And Location: Contact surfaces silver Precious Material: Silver Style Designator: Tap, square frame Thread Series Designator: Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No Fiig: A052b0