

View Online at <https://aerobasegroup.com/nsn/5930-00-365-8851>

Hazardous Locations/environmental Protection:

Dustproof and moisture proof

Overall Length:

1.250 inches

Body Length:

0.750 inches

Overall Diameter:

0.391 inches

Unthreaded Mounting Hole Diameter:

0.112 inches

Distance Between Mounting Facility Centers:

1.000 inches

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

150.0 degrees celsius and -65.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.5 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+24.00/+150.00 actuation point degrees celsius and +24.00/+150.00 deactuation point degrees celsius

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

106.00 actuation point degrees fahrenheit and 73.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0