NSN 5930-00-366-5060

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

Dustproof

Overall Length: 0.800 inches



View Online at https://aerobasegroup.com/nsn/5930-00-366-5060

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches
Overall Height:
0.519 inches
Overall Width:
0.250 inches
Body Length:
0.800 inches
Body Width:
0.250 inches
Body Height:
0.394 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.062 inches
Actuator Height:
0.030 inches
Actuator Free Position Height:
0.363 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
5.0 ounces
Actuator Movement:
Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

NSN 5930-00-366-5060

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac

Special Features:

Temperature limit plus 400 degree fahrenheit

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0