NSN 5930-00-366-5060

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-366-5060

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.800 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

0.519 inches

Overall Width:

0.250 inches

Body Length:

0.800 inches

Body Width:

0.250 inches

_

Body Height:

0.394 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.062 inches

Actuator Height:

0.030 inches

Actuator Free Position Height:

0.363 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

NSN 5930-00-366-5060

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac

Special Features:

Temperature limit plus 400 degree fahrenheit

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0