

View Online at <https://aerobasegroup.com/nsn/5930-00-368-4110>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.150 inches

Body Length:

0.300 inches

Body Width:

0.100 inches

Body Height:

0.250 inches

Unthreaded Mounting Hole Diameter:

0.062 inches

Actuator Style:

Leaf

Actuator Width:

0.080 inches

Actuator Free Position Height:

0.368 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.32 grams

Switch Actuating Force:

2.33 grams

Actuator Movement:

Between 0.090 pretravel inches and 0.014 overtravel inches and 0.021 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac

Test Data Document:

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0