NSN 5930-00-369-1045



| Pressure Switch - Page 1 of 2 | Group |
|---|-------|
| View Online at https://aerobasegroup.com/nsn/5930-00-369-1045 | |
| Thread Class: | |
| 3a single pressure connection | |
| Thread Length: | |
| 0.281 inches single pressure connection | |
| Overall Length: | |
| 3.703 inches | |
| Outside Diameter: | |
| 0.438 inches single connection | |
| Body Diameter: | |
| 0.880 inches | |
| Body Length: | |
| 3.250 inches | |
| Overall Diameter: | |
| 1.250 inches | |
| Pressure Switch Type: | |
| Gage | |
| Operating Tempurature Rating: | |
| Between -40.0 degrees fahrenheit and 275.0 degrees fahrenheit | |
| Mounting Method: | |
| Clamp | |
| Features Provided: | |
| Electrical box connector | |
| Thready Qty Per Inch (tpi): | |
| 20 single pressure connection | |
| Contact Action Stimulus: | |
| Increase | |
| Proof Pressure: | |

4500.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

7500.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

100.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

2100.00 actuation point pounds per square inch gage and 1800.00 deactuation point pounds per square inch gage and 300.00 differential point pounds per square inch gage

NSN 5930-00-369-1045

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 28.0 dc at sea level single voltage Pressure Connector Type: Flared, threaded external single connection Media For Which Designed: Liquid Style Designator: Cylindrical Thread Series Designator: Unf single pressure connection Shelf Life: N/a Unit Of Measure:

Demilitarization:

No Fiig: A048b0