## NSN 5930-00-369-8025

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-369-8025

Thread Class:					
3a single threaded bushing					
Overall Length:					
2.438 inches					
Body Diameter:					
0.312 inches					
Body Length:					
1.031 inches					
Tempurature Sensing Element Type:					
Immersion well					
Width Across Flats:					
0.750 inches					
Mounting Method:					
Threaded bushing					
Features Provided:					
Electrical box connector					
Thready Qty Per Inch (tpi):					
20 single threaded bushing					
Contact Action Stimulus:					
Decrease					
Thread Size:					
0.500 inches single threaded bushing					
Nonpile-up Contact Arrangement:					
1 pole, single throw, normally open, momentary action					
Terminal Type:					
Connector, receptacle					
Contact Load Current Patings					
Contact Load Current Rating:					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage Contact Adjustability:					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  107.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  107.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  107.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  28.0 dc at sea level second voltage					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  107.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  28.0 dc at sea level second voltage  Media For Which Designed:					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  107.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  28.0 dc at sea level second voltage  Media For Which Designed:  Gas or liquid					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  107.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  28.0 dc at sea level second voltage  Media For Which Designed:  Gas or liquid  Style Designator:					
2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point not adjustable  Contact Stimulus Rating:  107.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:  28.0 dc at sea level second voltage  Media For Which Designed:  Gas or liquid  Style Designator:  Cylindrical w/flange					

N/a

## NSN 5930-00-369-8025

Thermostatic Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A048b0