NSN 5930-00-369-8485

Rotary Switch Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-369-8485

Overall Height:1.875 inchesOverall Width:1.625 inchesBody Thickness:0.062 inchesSwitch Contact Basic Design:Nonpile-up nonsymmetricalMounting Method:Strut single mounting facilityContact Voltage Rating In Volts:28.0 dc at sea levelTerminal Type:Tab, solder lugContact Load Current Rating:S00.0 milliamperes resistive load ac at sea levelPrecious Material And Location:Contacts and rotor blade surfaces silverPrecious Material:SilverShelf Life:N/aUnit Of Measure:Penillitarization:NoFig:	1.875 inches Overall Width: 1.625 inches Body Thickness: 0.062 inches Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Overall Width:1.625 inchesBody Thickness:0.062 inchesSwitch Contact Basic Design:Nonpile-up nonsymmetricalMounting Method:Strut single mounting facilityContact Voltage Rating In Volts:28.0 dc at sea levelTerminal Type:Tab, solder lugContact Load Current Rating:500.0 milliamperes resistive load ac at sea levelPrecious Material And Location:Contacts and rotor blade surfaces silverPrecious Material:SilverStyle Designator:Switch section, rotaryShelf Life:N/aUnit Of Measure:Demilitarization:No	Overall Width:1.625 inchesBody Thickness:0.062 inchesSwitch Contact Basic Design:Nonpile-up nonsymmetricalMounting Method:Strut single mounting facilityContact Voltage Rating In Volts:28.0 dc at sea levelTerminal Type:Tab, solder lugContact Load Current Rating:500.0 milliamperes resistive load ac at sea levelPrecious Material And Location:Contacts and rotor blade surfaces silverPrecious Material:SilverStyle Designator:Switch section, rotaryShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Overall Height:
1.625 inches Body Thickness: 0.062 inches Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: So0.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	1.625 inches Body Thickness: O.062 inches Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: S00.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.875 inches
Body Thickness: 0.062 inches Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Silver Sityle Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Thickness: 0.062 inches Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Overall Width:
0.062 inches Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.062 inches Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: T No Fig:	1.625 inches
Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: 	Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Thickness:
Nonpile-up nonsymmetrical Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Nonpile-up nonsymmetricalMounting Method:Strut single mounting facilityContact Voltage Rating In Volts:28.0 dc at sea levelTerminal Type:Tab, solder lugContact Load Current Rating:500.0 milliamperes resistive load ac at sea levelPrecious Material And Location:Contacts and rotor blade surfaces silverPrecious Material:SilverStyle Designator:Switch section, rotaryShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	0.062 inches
Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Mounting Method: Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Switch Contact Basic Design:
Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Strut single mounting facility Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Nonpile-up nonsymmetrical
Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Contact Voltage Rating In Volts: 28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mounting Method:
28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	28.0 dc at sea level Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Strut single mounting facility
Terminal Type:Tab, solder lugContact Load Current Rating:500.0 milliamperes resistive load ac at sea levelPrecious Material And Location:Contacts and rotor blade surfaces silverPrecious Material:SilverStyle Designator:Switch section, rotaryShelf Life:N/aUnit Of Measure:Demilitarization:No	Terminal Type:Tab, solder lugContact Load Current Rating:500.0 milliamperes resistive load ac at sea levelPrecious Material And Location:Contacts and rotor blade surfaces silverPrecious Material:SilverStyle Designator:Switch section, rotaryShelf Life:N/aUnit Of Measure:NoFiig:	Contact Voltage Rating In Volts:
Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	28.0 dc at sea level
Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type:
500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	500.0 milliamperes resistive load ac at sea level Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tab, solder lug
Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization:	Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Contact Load Current Rating:
Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	500.0 milliamperes resistive load ac at sea level
Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Precious Material: Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Precious Material And Location:
Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Silver Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Contacts and rotor blade surfaces silver
Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Style Designator: Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Precious Material:
Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No	Switch section, rotary Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Silver
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No	N/a Unit Of Measure: Demilitarization: No Fiig:	Switch section, rotary
Unit Of Measure: Demilitarization: No	Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No	 Demilitarization: No Fiig:	N/a
Demilitarization: No	Demilitarization: No Fiig:	Unit Of Measure:
No	No Fiig:	
	Fiig:	Demilitarization:
Fiig:	-	No
	A052b0	Fiig:
A052b0		A052b0