

View Online at <https://aerobasegroup.com/nsn/5930-00-371-1934>

Thread Class:

3a all pressure connection

Thread Length:

0.378 inches second pressure connection

Overall Length:

2.853 inches

Outside Diameter:

0.375 inches all connections

Body Diameter:

1.750 inches

Overall Diameter:

3.500 inches

Pressure Switch Type:

Differential

Mounting Method:

Input port

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

24 first pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

9.00 pounds per square inch

Thread Size:

0.438 inches second pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

16.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

2.00 actuation point inches of water and 1.00 deactuation point inches of water and 1.00 differential point inches of water

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external all connections

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0