

View Online at <https://aerobasegroup.com/nsn/5930-00-371-2848>

Thread Length:

0.500 inches single mounting facility

Hazardous Locations/environmental Protection:

Shock proof and vibration proof

Overall Length:

4.875 inches

First Flat Length:

0.312 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.875 inches single actuator

Overall Diameter:

1.625 inches

Nonturn Device Radius:

0.531 inches at 9: 00 o'clock

Individual Section Quantity:

10

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

8 each section rear

Mounting Method:

Threaded bushing single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Shaft Flat/slot Angular Location:

330.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

9 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0