## NSN 5930-00-372-2740

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-372-2740

**Thread Length:** 

0.312 inches single mounting facility

**Overall Length:** 

1.406 inches

**Shaft Diameter:** 

0.248 inches single actuator

**Shaft Length:** 

0.281 inches single actuator

**Overall Diameter:** 

1.000 inches

**Individual Section Quantity:** 

1

**Operating Tempurature Range:** 

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 single section rear

**Throw Quantity:** 

4 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

Shaft Type:

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section front

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Contact Load Current Rating:** 

200.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

## **Test Data Document:**

81349-mil-s3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef single mounting facility

## NSN 5930-00-372-2740

Rotary Switch - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0