

View Online at <https://aerobasegroup.com/nsn/5930-00-374-9927>

Thread Length:

0.438 inches single pressure connection

Overall Length:

2.469 inches

Outside Diameter:

0.125 inches single connection

Body Length:

1.844 inches

Overall Diameter:

1.094 inches

Pressure Switch Type:

Absolute

Mounting Method:

Input port

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

125.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

30.00 actuation point pounds per square inch absolute and 32.00 deactuation point pounds per square inch absolute and 2.00 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Inverted flare, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0