

View Online at <https://aerobasegroup.com/nsn/5930-00-375-5478>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

6.750 inches

Overall Height:

2.938 inches

Overall Width:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.250 inches single mounting facility

Individual Section Quantity:

2

Knob Manufacturer Code:

28339

Knob Manufacturer Part Number:

K-6046075-1

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

1 each section front

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

600.0 highest dc voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

6.0 amperes resistive load lowest dc voltage rating at sea level and 4.0 amperes inductive load lowest dc voltage rating at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0