## NSN 5930-00-375-5659

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-375-5659

Hazardous Locations/environmental Protection:
Dustproof
Overall Height:
3.250 inches
Overall Width:
4.375 inches
Shaft Length:
1.000 inches single actuator
Unthreaded Mounting Hole Diameter:
0.312 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9000s6202-73075pc1
Longest Horizontal Distance Between Mounting Centers:
3.750 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.625 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
3 each section front
Mounting Method:
Base single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
1000.0 dc at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Square Shaft Size:
0.150 inches single actuator and 0.151 inches single actuator
Terminal Type:
Tab w/screw

## NSN 5930-00-375-5659

Rotary Switch - Page 2 of 2



C	nta	ct	Sw	itcl	nina	ιΔc	tion	١,
v	JIILO	ıυι	JW	ILLI	HILL	H	เเบเ	١.

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

**Contact Load Current Rating:** 

2.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A052b0