NSN 5930-00-375-5891

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-375-5891

Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
3.280 inches
Overall Height:
2.500 inches
Overall Width:
3.000 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
4
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
2 each section rear
Mounting Facility Circle Radius:
0.221 inches single mounting facility
Mounting Method:
Mounting Method.
Bracket single mounting facility and unthreaded hole single mounting facility
-
Bracket single mounting facility and unthreaded hole single mounting facility
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided:
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts:
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level Mounting Facility Pattern:
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level Mounting Facility Pattern: Four position circular single mounting facility
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity:
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type:
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action:
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front Switch Actuator Positioning Increment:
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front Switch Actuator Positioning Increment: 90.0 degrees single actuator
Bracket single mounting facility and unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts: 125.0 ac at sea level120.0 dc at sea level Mounting Facility Pattern: Four position circular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section front Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating:

N/a

Shelf Life:

NSN 5930-00-375-5891 Rotary Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A052b0