NSN 5930-00-377-9991

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-377-9991

| Body Style: |
|--|
| Hole mounted |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.375 inches |
| Body Length: |
| 0.781 inches |
| Body Width: |
| 0.250 inches |
| Body Height: |
| 0.484 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.088 inches |
| Actuator Length: |
| 0.781 inches |
| Actuator Style: |
| Leaf |
| Actuator Width: |
| 0.125 inches |
| Actuator Free Position Height: |
| 0.536 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 10.0 grams |
| Switch Actuating Force: |
| 56.0 grams |
| Actuator Movement: |
| Between 0.156 pretravel inches and 0.040 overtravel inches and 0.020 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 10.100 amperes resistive ac |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5930-00-377-9991

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0