

View Online at <https://aerobasegroup.com/nsn/5930-00-386-9172>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Weatherproof

Body Diameter:

1.030 inches

Bushing Length:

Between 0.970 inches and 1.030 inches

Body Length:

1.200 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.400 inches

Actuator Free Position Height:

0.430 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing w/panel seal

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.500 amperes inductive dc and 1.000 amperes motor dc

Thread Series Designator:

Unf

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0