

View Online at <https://aerobasegroup.com/nsn/5930-00-386-9172>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Weatherproof

**Body Diameter:**

1.030 inches

**Bushing Length:**

Between 0.970 inches and 1.030 inches

**Body Length:**

1.200 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.400 inches

**Actuator Free Position Height:**

0.430 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing w/panel seal

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

192.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.500 amperes inductive dc and 1.000 amperes motor dc

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

12 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0