

View Online at <https://aerobasegroup.com/nsn/5930-00-387-2485>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture proof

Body Diameter:

0.630 inches

Bushing Length:

0.710 inches

Body Length:

1.410 inches

Case Material:

Metal

Actuator Height:

0.500 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Anttc38

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing w/panel seal

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Terminals gold and contact surfaces silver

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0