

View Online at <https://aerobasegroup.com/nsn/5930-00-387-2608>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

5.000 inches

**Overall Height:**

3.344 inches

**Overall Width:**

3.344 inches

**Individual Section Quantity:**

6

**Longest Horizontal Distance Between Mounting Centers:**

3.219 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.281 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

6 each section rear

**Throw Quantity:**

1 each section rear

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

20 single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

120.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level and 25.0 amperes inductive load dc at sea level and 30.0 amperes lamp load dc at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Un single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0