

View Online at <https://aerobasegroup.com/nsn/5930-00-387-2686>

Overall Length:

1.578 inches

Body Length:

1.016 inches

Pressure Switch Type:

Absolute

Width Across Flats:

0.719 inches

Mounting Method:

Clamp

Thread Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

7500.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

7.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

15.00 actuation point pounds per square inch and 10.00 deactuation point pounds per square inch and 5.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0