## NSN 5930-00-391-4772

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-391-4772					
Thread Class:					
2b single mounting facility					
Hazardous Locations/environmental Protection:					
Dustproof					
Overall Height:					
4.688 inches					
Overall Width:					
2.875 inches					
Shaft Length:					
0.688 inches single actuator					
Individual Section Quantity:					
2					
Knob Manufacturer Code:					
71669					
Knob Manufacturer Part Number:					
K6004154f31					
Longest Horizontal Distance Between Mounting Centers:					
1.875 inches single mounting facility					
Switch Contact Basic Design:					
Nonpile-up symmetrical					
Pole Quantity:					
2 each section front					
Throw Quantity:					
2 each section front					
Mounting Method:					
Base single mounting facility and threaded hole single mounting facility					
Features Provided:					
Actuator knob					
Thready Qty Per Inch (tpi):					
20 single mounting facility					
Thread Size:					
0.250 inches single mounting facility					
Contact Voltage Rating In Volts:					
600.0 highest ac voltage rating at sea level					
Mounting Facility Pattern:					
Two position in-line single mounting facility					
Switch Actuator Indexing Position Quantity:					
4 single actuator					
Shaft Type:					
Rectangular/square, threaded hole single actuator					
Terminal Type:					

Tab w/screw

## NSN 5930-00-391-4772

Rotary Switch - Page 2 of 2



Conta	ct Sv	vitchin	a Act	ion:
oonta	10L 01	VILCIIII :	I ACL	IVII.

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## **Contact Load Current Rating:**

6.0 amperes resistive load highest dc voltage rating at sea level

Style Designator:

In-line, cam actuated

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0