NSN 5930-00-391-4772

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-391-4772
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Height:
4.688 inches
Overall Width:
2.875 inches
Shaft Length:
0.688 inches single actuator
Individual Section Quantity:
2
Knob Manufacturer Code:
71669
Knob Manufacturer Part Number:
K6004154f31
Longest Horizontal Distance Between Mounting Centers:
1.875 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section front
Throw Quantity:
2 each section front
Mounting Method:
Base single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
20 single mounting facility
Thread Size:
0.250 inches single mounting facility
Contact Voltage Rating In Volts:
600.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Two position in-line single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Terminal Type:

Tab w/screw

NSN 5930-00-391-4772

Rotary Switch - Page 2 of 2



Con	tact	Swit	chino	ı Acti	on:
OUL	ıavı	OWIL	CHILL	ı Actı	vii.

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

6.0 amperes resistive load highest dc voltage rating at sea level

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0