

View Online at <https://aerobasegroup.com/nsn/5930-00-391-5681>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.094 inches

Body Width:

0.406 inches

Body Height:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

2.577 inches

Actuator Style:

Leaf

Actuator Width:

0.125 inches

Actuator Free Position Height:

0.500 inches

Maximum Voltage Rating In Volts:

125.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

2.0 ounces

Actuator Movement:

Between 0.500 pretravel inches and 0.312 overtravel inches and 0.100 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0