NSN 5930-00-391-5685

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-391-5685

Body Style: Bushing mounted Body Diameter: Between 0.350 inches and 0.370 inches Bushing Length: Between 0.240 inches and 0.260 inches Body Length: 0.500 inches Case Material: Plastic Actuator Diameter: Between 0.175 inches and 0.195 inches Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Body Diameter: Between 0.350 inches and 0.370 inches Bushing Length: Between 0.240 inches and 0.260 inches Body Length: 0.500 inches Case Material: Plastic Actuator Diameter: Between 0.175 inches and 0.195 inches Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Between 0.350 inches and 0.370 inches Bushing Length: Between 0.240 inches and 0.260 inches Body Length: 0.500 inches Case Material: Plastic Actuator Diameter: Between 0.175 inches and 0.195 inches Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Bushing Length: Between 0.240 inches and 0.260 inches Body Length: 0.500 inches Case Material: Plastic Actuator Diameter: Between 0.175 inches and 0.195 inches Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Between 0.240 inches and 0.260 inches Body Length: 0.500 inches Case Material: Plastic Actuator Diameter: Between 0.175 inches and 0.195 inches Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Body Length: 0.500 inches Case Material: Plastic Actuator Diameter: Between 0.175 inches and 0.195 inches Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
0.500 inches Case Material: Plastic Actuator Diameter: Between 0.175 inches and 0.195 inches Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Case Material: Plastic Actuator Diameter: Between 0.175 inches and 0.195 inches Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Plastic Actuator Diameter: Between 0.175 inches and 0.195 inches Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Actuator Diameter: Between 0.175 inches and 0.195 inches Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Between 0.175 inches and 0.195 inches Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Actuator Height: 0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
0.187 inches Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Actuator Color: Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Red single actuator Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Illuminated Actuator Color: Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Red single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
115.0 ac and 28.0 dc
Inclosure Type:
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
40
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
2.000 amperes resistive dc and 100.000 milliamperes resistive ac
Special Features:
Special Features: Light source; non-replicable light emitting diode
•
Light source; non-replicable light emitting diode
Light source; non-replicable light emitting diode Thread Series Designator:
Light source; non-replicable light emitting diode Thread Series Designator: Uns
Light source; non-replicable light emitting diode Thread Series Designator: Uns Terminal Type And Quantity:
Light source; non-replicable light emitting diode Thread Series Designator: Uns Terminal Type And Quantity: 4 pin

--

NSN 5930-00-391-5685

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0