## NSN 5930-00-392-5488

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-392-5488

Hole mounted

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

#### **Body Width:**

0.687 inches

Body Height:

1.150 inches

## **Unthreaded Mounting Hole Diameter:**

0.140 inches

Actuator Length:

1.050 inches

Actuator Style:

Roller arm

## **Actuator Free Position Height:**

1.266 inches

Actuator Roller Diameter:

0.370 inches

Actuator Roller Width:

0.250 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

1.5 ounces

#### Switch Actuating Force:

6.0 ounces

## **Actuator Movement:**

Between 0.094 pretravel inches and 0.040 overtravel inches and 0.020 differential inches

## Contact Load Current Rating At Maximum Rated Voltage:

150.000 milliamperes resistive dc and 15.000 amperes resistive ac

## Terminal Type And Quantity:

3 screw

### Shelf Life:

N/a

# NSN 5930-00-392-5488

Sensitive Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

