NSN 5930-00-392-5579

Pressure Switch - Page 1 of 2

Pressure Connector Type:

Plain, threaded external single connection



View Online at https://aerobasegroup.com/nsn/5930-00-392-5579

Thread Length:
0.500 inches single pressure connection
Overall Length:
2.750 inches
Outside Diameter:
0.750 inches single connection
Overall Height:
4.375 inches
Overall Width:
1.375 inches
Body Height:
3.250 inches
Pressure Switch Type:
Differential
Mounting Method:
Line
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
14 single pressure connection
Contact Action Stimulus:
Decrease
Thread Size:
0.750 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
15.0 amperes resistive load second voltage
Contact Adjustability:
Actuation point adjustable and deactuation point not adjustable
Contact Adjustment Range:
+2.00/+20.00 actuation point pounds per square inch gage
Contact Adjustment Type:
External actuation point hex nut
Contact Stimulus Rating:
0.00 deactuation point pounds per square inch gage and 17.50 deactuation point pounds per square inch gage
Contact Voltage Rating In Volts:
240.0 ac at sea level second voltage

NSN 5930-00-392-5579

Pressure Switch - Page 2 of 2



Frequency In Hertz:
60.0 second voltage
Media For Which Designed:
Liquid
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Nptf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0