NSN 5930-00-394-0733

Sensitive Switch - Page 1 of 2

1 connector, receptacle



View Online at https://aerobasegroup.com/nsn/5930-00-394-0733

Body Style:
Bushing/hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.625 inches
Bushing Length:
0.720 inches
Body Length:
3.125 inches
Body Width:
1.440 inches
Unthreaded Mounting Hole Diameter:
0.218 inches
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.375 inches
Actuator Free Position Height:
1.470 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing and threaded hole
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
80.0 ounces
Switch Actuating Force:
192.0 ounces
Actuator Movement:
Between 0.070 pretravel inches and 0.250 overtravel inches and 0.045 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive ac
Thread Series Designator:
Unf
Terminal Type And Quantity:

NSN 5930-00-394-0733

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0