## NSN 5930-00-396-3684

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-396-3684

**Thread Class:** 3a single pressure connection **Thread Length:** 0.250 inches single pressure connection **Overall Length:** 2.620 inches **Outside Diameter:** 0.438 inches single connection **Body Length:** 1.508 inches **Overall Diameter:** 0.750 inches **Pressure Switch Type:** Gage **Operating Tempurature Rating:** Between -34.0 degrees celsius and 74.0 degrees celsius **Mounting Method:** Clamp Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Increase **Proof Pressure:** 150.00 pounds per square inch **Thread Size:** 0.438 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 1.0 amperes resistive load single voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 30.00 actuation point pounds per square inch gage and 15.00 deactuation point pounds per square inch gage **Contact Voltage Rating In Volts:** 28.0 dc at sea level single voltage **Pressure Connector Type:** 

## Frequency In Hertz:

Flared, threaded external single connection

60.0 single voltage

## **NSN 5930-00-396-3684** Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0