NSN 5930-00-396-3684

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-396-3684

Thread Class:

3a single pressure connection

Thread Length:

0.250 inches single pressure connection

Overall Length:

2.620 inches

Outside Diameter:

0.438 inches single connection

Body Length:

1.508 inches

Overall Diameter:

0.750 inches

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -34.0 degrees celsius and 74.0 degrees celsius

Mounting Method:

Clamp

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

30.00 actuation point pounds per square inch gage and 15.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Frequency In Hertz:

60.0 single voltage

NSN 5930-00-396-3684

Pressure Switch - Page 2 of 2



Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0