

View Online at <https://aerobasegroup.com/nsn/5930-00-396-6862>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Weatherproof

Body Diameter:

0.469 inches

Bushing Length:

0.900 inches

Body Length:

0.500 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 0.510 inches and 0.540 inches

Actuator Roller Diameter:

Between 0.421 inches and 0.591 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

24.0 ounces

Switch Actuating Force:

14.0 ounces

Actuator Movement:

Between 0.010 pretravel inches and 0.125 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes lamp dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0