

View Online at <https://aerobasegroup.com/nsn/5930-00-396-7890>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

0.890 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.094 inches

Actuator Free Position Height:

0.660 inches

Maximum Voltage Rating In Volts:

480.0 ac

End Application:

Emory s.Land class as, strgeon class ssn (637), spruance class d (963), forrestal class cv, oliver perry class ffg, whidbey island class lsd, nimitz class cvn, kidd class ddg, cimmaron class ao, system, 02n2.

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

14.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.005 overtravel inches and 0.0006 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0