## NSN 5930-00-396-7890

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-396-7890

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.890 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Free Position Height:
0.660 inches
Maximum Voltage Rating In Volts:
480.0 ac
End Application:
Emory s.Land class as, strgeon class ssn (637), spruance class d (963), forrestal class cv, oliver perry class ffg, whidbey island class Iso
nimitz class cvn, kidd class ddg, cimmaron class ao, system, 02n2.
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
14.0 ounces
Actuator Movement:
Between 0.020 pretravel inches and 0.005 overtravel inches and 0.0006 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive ac
Special Features:

3 tab w/screw

Weapon system essential

Terminal Type And Quantity:

## NSN 5930-00-396-7890

Sensitive Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0