

View Online at <https://aerobasegroup.com/nsn/5930-00-397-8467>

Thread Class:

2b all pressure connection

Inside Diameter:

0.438 inches all connections

Overall Length:

5.188 inches

Overall Height:

7.750 inches

Overall Width:

2.812 inches

Body Length:

5.000 inches

Body Height:

7.000 inches

Unthreaded Mounting Hole Diameter:

0.562 inches

Distance Between Mounting Facility Centers:

4.000 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Decrease

Proof Pressure:

60.00 pounds per square inch gage

Thread Size:

0.438 inches all pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load fifth voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+8.00/+50.00 actuation point inches of water

Contact Adjustment Type:

Internal actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level eighth voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0