NSN 5930-00-399-7764

Rotary Switch - Page 1 of 2



930-00-399-7764

| View Online at https://aerobasegroup.com/nsn/59 |
|---|
| Thread Length: |
| 0.375 inches single mounting facility |
| Overall Length: |
| 2.437 inches |
| Overall Height: |
| 1.875 inches |
| Overall Width: |
| 1.625 inches |
| First Flat Length: |
| 0.313 inches single actuator |
| Flat Height: |
| 0.216 inches single actuator |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 0.813 inches single actuator |
| Individual Section Quantity: |
| 2 |
| Operating Tempurature Range: |
| -25.0/+85.0 degrees celsius |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section rear |
| Throw Quantity: |
| 5 each section rear |
| Mounting Method: |
| Threaded bushing single mounting facility |
| Thread Size: |
| 0.375 inches single mounting facility |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level |
| Switch Actuator Indexing Position Quantity: |
| 6 single actuator |
| Shaft Type: |
| Round, flatted single actuator |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |
| Breaks before makes each section rear |
| Switch Actuator Positioning Increment: |

60.0 degrees single actuator

NSN 5930-00-399-7764

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0