NSN 5930-00-400-1758

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-400-1758

Thread Class:

2a 2nd mounting facility

Thread Length:

0.500 inches 2nd mounting facility

Overall Length:

9.938 inches

Shaft Length:

0.344 inches single actuator

Unthreaded Mounting Hole Diameter:

0.219 inches 1st mounting facility

Individual Section Quantity:

20

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

7 each section rear

Mounting Facility Circle Radius:

1.625 inches 1st mounting facility

Mounting Method:

Threaded stud 2nd mounting facility

Features Provided:

Actuator knob

Thread Size:

0.073 inches 2nd mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Four position circular 1st mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

NSN 5930-00-400-1758

Rotary Switch - Page 2 of 2



Cc	ntact	I nad	Current	Rating:
·ι	пиасі	Luau	Current	naunu.

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0