

View Online at <https://aerobasegroup.com/nsn/5930-00-400-1820>

Body Style:

Bushing mounted

Bushing Length:

Between 0.290 inches and 0.330 inches

Body Length:

1.210 inches

Body Width:

0.850 inches

Body Height:

5.000 inches

Actuator Diameter:

Between 0.308 inches and 0.338 inches

Actuator Height:

Between 0.180 inches and 0.220 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Test Data Document:

81349-mil-prf-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Specification Data:

81349-mil-prf-8805/23 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A053a0

Mil-std (military Standard):

Mil-prf-8805 spec.