

View Online at <https://aerobasegroup.com/nsn/5930-00-400-6214>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

1.187 inches

Overall Height:

2.031 inches

Overall Width:

0.625 inches

Bushing Length:

0.469 inches

Body Width:

0.625 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

Oliver perry class ffg, forrestal class cv, waters class tags-45. Intergrated underwater surviellance systems, galley equipment & food service. Strategic sealift conversion ships class. Over the horizon back scanner (oth-b) program (an/fps-118). Lgm-30 minuteman missle; 3990-01-444-6174 bitum distributor

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0