NSN 5930-00-400-9890

Thermostatic Switch - Page 1 of 2

Hazardous Locations/environmental Protection:

Thread Class:
2a all threaded stud
Thread Length:

Dustproof

Gas

0.187 inches all threaded stud



View Online at https://aerobasegroup.com/nsn/5930-00-400-9890

Overall Height: 0.541 inches **Body Height:** 0.320 inches **Overall Diameter:** 0.620 inches **Tempurature Sensing Element Type:** Internal sensor **Operating Tempurature Rating:** 125.0 degrees celsius and -65.0 degrees celsius **Mounting Method:** Threaded stud Thready Qty Per Inch (tpi): 32 all threaded stud **Contact Action Stimulus:** Increase **Thread Size:** 0.138 inches all threaded stud **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 5.0 amperes resistive load third voltage and 1.0 amperes inductive load third voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 265.00 actuation point degrees fahrenheit and 235.00 deactuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 28.0 dc at sea level third voltage **Special Features:** Not provided with visual indicating thermometer Frequency In Hertz: 400.0 second voltage Media For Which Designed:

NSN 5930-00-400-9890

Thermostatic Switch - Page 2 of 2



Style Designator:
Disc
Thread Series Designator:
Unc all threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0