

View Online at <https://aerobasegroup.com/nsn/5930-00-401-6508>

Thread Class:

2a all threaded stud

Thread Length:

0.375 inches all threaded stud

Hazardous Locations/environmental Protection:

Moisture proof

Overall Height:

0.781 inches

Body Height:

0.290 inches

Overall Diameter:

0.605 inches

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

Between -30.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Threaded stud

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

6.0 amperes resistive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

255.00 actuation point degrees fahrenheit and 240.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas

Style Designator:

Disc

Thread Series Designator:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0