NSN 5930-00-401-6536

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-401-6536 **Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 4.396 inches **Overall Height:** 1.531 inches **Overall Width:** 1.312 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.125 inches single actuator **Nonturn Device Radius:** 0.531 inches at 8: 00 o'clock **Individual Section Quantity:** 2 **Nonturn Device Type:** Tab at 8: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 2nd section rear **Throw Quantity:** 5 2nd section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 5 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

NSN 5930-00-401-6536

Rotary Switch - Page 2 of 2



| Switch Actuator Stop Device Type: |
|--|
| Fixed stop single actuator |
| Contact Load Current Rating: |
| 1.0 amperes resistive load ac at sea level |
| Precious Material And Location: |
| Contacts silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Circular wafer, bushing mount |
| Thread Series Designator: |
| Unef single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A052b0