## NSN 5930-00-401-6706

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-401-6706

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.250 inches single mounting facility

**Overall Height:** 

1.312 inches

**Overall Width:** 

1.281 inches

**Shaft Diameter:** 

0.250 inches single actuator

**Nonturn Device Radius:** 

0.531 inches at 3: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Contact Load Current Rating:** 

500.0 milliamperes resistive load ac at sea level

**Precious Material And Location:** 

Contact surfaces silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

## NSN 5930-00-401-6706

Rotary Switch - Page 2 of 2



| C | ha  | Ιf | 1 | ife   |  |
|---|-----|----|---|-------|--|
| • | ııe |    | _ | .II C |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0