

View Online at <https://aerobasegroup.com/nsn/5930-00-401-6738>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Explosion proof

**Body Diameter:**

1.030 inches

**Bushing Length:**

0.470 inches

**Body Length:**

1.800 inches

**Actuator Style:**

Round

**Actuator Height:**

Between 0.660 inches and 0.720 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary

**Maximum Voltage Rating In Volts:**

26.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes lamp dc and 2.000 amperes inductive ac

**Special Features:**

Solenoid capable of holding both poles in the momentary position when selected

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0