

View Online at <https://aerobasegroup.com/nsn/5930-00-401-7276>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches

**Body Length:**

1.093 inches

**Body Width:**

0.400 inches

**Body Height:**

0.625 inches

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Actuator Length:**

0.156 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.172 inches

**Actuator Free Position Height:**

0.640 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

14.0 ounces

**Actuator Movement:**

Between 0.047 pretravel inches and 0.031 overtravel inches and 0.014 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes inductive dc and 15.000 amperes inductive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0